ENVIRONMENTAL & TECHNICAL PRODUCT DATA SHEET

POPLAR PLYWOOD

PANGUANETA
PLYWOOD FOR LIFE

Environmental & Technical Assurance



ILOMBA FACED

Ilomba construction giving significant weight saving and very high quality faces

Hanson Ilomba Plywood is available in a number of thicknesses. Composed of Ilomba and poplar, Ilomba Twin performs much the same as poplar throughout plywood with the added decorative quality of pink-hued, Ilomba face and back veneers.

SPECIFICATION DETAIL

Thickness Range	3mm-40mm
Dimensions (mm)	2500 x 1200
Average Density	400 kg/m³ ± 10%
Product Classification	BS EN 636-1
Glue Bond	BS EN 314-2 Class 1
Formaldehyde Class	E1
Moisture Content	8%-13%
Veneers	High quality face and core
Face Grade	B/BB
Chain of Custody Status	PEFC (FSC® available on request)
DOP (Declaration of performance)	Available on request
CE Marked	BS EN 13986
Material Safety Data Sheet	Available on request

APPLICATIONS

- LAMINATING/VENEERING
- COMMERCIAL/LEISURE VEHICLES
- FURNITURE
- BOAT/YACHT BUILDING
- EXHIBITION/DISPLAYS
- SHOP/BAR FITTING
- CONSTRUCTION/JOINERY
- LASER CUTTING
- TOY/MODEL MAKING
- THEATRE SETS



Hanson
PLYWOOD LIMITED

Talk to a member of our technical team for more information

Hanson Plywood Limited
Drakes Industrial Estate, Shay Lane
Ovenden, Halifax HX3 6RL

Tel: 01422 330444 **Fax:** 01422 330706
Email: sales@hanson-plywood.co.uk
www.hanson-plywood.co.uk

NBS Source

TIMBER DEVELOPMENT UK

PlanetMark
Certified Business

© HANSON PLYWOOD LIMITED 2023