ENVIRONMENTAL & TECHNICAL PRODUCT DATA SHEET

POPLAR PLYWOOD

PANGUANETA
PLYWOOD FOR LIFE

Environmental & Technical Assurance



POPLAR THROUGHOUT

Poplar construction giving significant weight saving and very high quality faces

Poplar throughout offers the user a lightweight, light colour, high homogeneity with a barely perceptible grain. Sustainable and extremely versatile for applications across many industries.

SPECIFICATION DETAIL

Thickness Range	3mm-30mm
Dimensions (mm)	2440 x 1220 ◆ 2500 x 1220 ◆ 3120 x 1220 ◆ 3050 x 1220
Average Density	400 kg/m³ ± 10%
Product Classification	BS EN 636-1
Glue Bond	BS EN 314-2 Class 1
Formaldehyde Class	E1
Moisture Content	8%-13%
Veneers	High quality face and core
Face Grades	AB/AB, B/BB
Chain of Custody Status	PEFC 100% (FSC® available on request)
EPD (Environmental Product Declaration)	Available (Click here)
DOP (Declaration of performance)	Available on request
CE Marked	BS EN 13986

APPLICATIONS

- LAMINATING/VENEERING
- COMMERCIAL/LEISURE VEHICLES
- FURNITURE
- BOAT/YACHT BUILDING
- EXHIBITION/DISPLAYS
- SHOP/BAR FITTING
- CONSTRUCTION/JOINERY
- LASER CUTTING
- TOY/MODEL MAKING
- THEATRE SETS



Hanson
PLYWOOD LIMITED

Talk to a member of our technical team for more information

Hanson Plywood Limited
Drakes Industrial Estate, Shay Lane
Ovenden, Halifax HX3 6RL

Tel: 01422 330444 **Fax:** 01422 330706
Email: sales@hanson-plywood.co.uk
www.hanson-plywood.co.uk

NBS Source

TIMBER DEVELOPMENT UK

PlanetMark
Certified Business

© HANSON PLYWOOD LIMITED 2023