

**CERTIFICATE OF COMPLIANCE
OF PRODUCTION CONTROL ON-SITE**

CE N° 0380 - CPR - 516

In the framework of the EU Regulation N° 305/2011 set forth by the European Parliament and the Council on 09 March, 2011, which harmonised the conditions to commercialise construction products and repealed Directive 89/106/CEE of the Council, it was established that for the following product:

PANGUA-FIRE - Peuplier

Thickness: 5 to 40 mm

Density: 450 kg/m³ (+/- 5%)

Classification: B-s1,d0 according to EN 13501-1

(european classification report n° FCBA 18/RC-68),

(Terms of use of the product: see attached annex)

Produced by: PANGUANETA SPA

**Manufactured in the facility located in:
Via Gino Solazzi 19 - - 46018 SABBIONETA (MN)
Italie**

FCBA, as the notified body N° 0380, determined the typical product on the basis of typical tests (including sampling), calculations concerning the type, values from tables or documentation describing the product; carried out the initial inspection of the fabrication facility and tested production on site, as well as carrying out surveillance, assessment and continuous approval of the on-site production (system 1).

The present certificate attests that all provisions concerning the conformity attestation of the on-site production set forth in the harmonised technical specification of reference **NF EN 13986: 2004 + A1 : 2015** have been applied.

This certificate was issued for the first time on **28/06/2019**, and except for withdrawal or suspension, shall remain valid as long as the conditions described in the harmonised technical specifications, production conditions on the site and production testing in the facility shall continue to conform.

The list of valid certificates of conformity can be accessed on the www.fcba.fr site.

(In case of litigation, only the French version of the present certificate is the authentic text).



CERTIFICATION
DE PRODUITS
ET SERVICES

ACCREDITATION N° 5-0011
PORTEE DISPONIBLE SUR
WWW.COFRAC.FR

Siège social
10, rue Galilée
77420 Champs-sur-Marne
Tél +33 (0)1 72 84 97 84
www.fcba.fr

Siret 775 680 903 00132
APE 7219Z
Code TVA CEE : FR 14 775 680 903

Institut technologique FCBA : Forêt, Cellulose, Bois – Construction, Ameublement

**Issued in CHAMPS-SUR-MARNE, /28/06/2019
N° 516/2019-GB**

For FCBA,
Certification Director
Alain HOCQUET



ANNEX

C Performance constancy Certificate
N° 516/2019-GB du /28/06/2019

CLASSIFICATION IS VALID IN TERMS OF USE FOLLOWING PRODUCT

« PANGUA-FIRE - Peuplier »:

The classification is valid for the following end use applications:

For thicknesses from 5 mm to less than 10 mm:

- mounting with mechanical fixation (nails, screws.) directly on the substrate,
- without air gap on a class A2-s1,d0 substrate or better with minimal density of 525 kg/m³ and minimal thickness of 12 mm (standard plaster board type).

For thicknesses from 10 mm to less than 18 mm:

- mounting with mechanical fixation (nails, screws.) on D-s2,d0 wood structure or better,
- without air gap on a class A2-s1,d0 substrate or better with minimal density of 525 kg/m³ and minimal thickness of 12 mm (standard plaster board type),
- the mounting is without air gap or with closed or open air gap of any thickness.

For thicknesses from 18 mm to 40 mm:

- mounting with mechanical fixation (nails, screws.) on D-s2,d0 wood structure or better,
- on a class D-s2,d0 substrate or better with minimal density of 510 kg/m³ and minimal thickness of 10 mm (standard particle board type), with or without protective rain screen rated E or better,
- the mounting is without air gap or with closed or open air gap of any thickness, according to table 8 of standard EN 13986.