

Birch Faced



PRODUCT DATA SHEET



SPECIFICATION DETAIL:

Plywood constructed with outer faces of birch veneers with poplar comprising the inner layers.

Our H Hanson Lightweight Panguaneta Plywood offers stability, ease of cutting and combines higher mechanical properties with the benefits of a lightweight panel.

Poplar/birch combi core is available on request. Outer faces are available in both long and cross grain directions. Birch faced poplar plywood is manufactured in accordance with the European and International standards.

Thicknesses (mm) 6mm-40mm 2440 x 1220 Dimensions (mm) 3050 x 1220 Average density 400 Kg/m³ ± 10% Product standard EN 636-1 Glue bond Class 1 (Interior) EN 314-2 Formaldehyde release Class E1 (tested to EN 717-2) Veneers High quality face and core Face grade B/BB PEFC[™] (FSC[®] available on request) **Environmental certification European Timber Regulation** Compliant - sourced within EU (EUTR) status **CE** marked BS EN 13986 Material safety data sheet Available

Shop/Bar fitting

Automotive

Applications

Boat/Yacht building

Furniture and design

Construction, architecture and general joinery

CONTACT: Drakes Industrial Estate Shay Lane, Halifax West Yorkshire HX3 6RL

Tel: 01422 330444 Fax: 01422 330706 Email: sales@hanson-plywood.co.uk www.hanson-plywood.co.uk



June 2020

For more information visit: www.hanson-plywood.co.uk





JBS PI





